



FEATURES & SPECIFICATIONS

INTENDED USE

To be powered by 6 or 12 volt battery equipment as part of an emergency lighting system providing light for the path of egress in Class 1, Division II environment.

CONSTRUCTION

Single or twin heads available.

Fully adjustable lamp heads meet all aiming requirements.

Lamp head constructed of lightweight, gray, thermoplastic and fully gasketed.

Removable bezel and slip-on lamp terminals simplify maintenance and lamp replacement.

Strong, compact and corrosion-resistant with a UL94V-0 flame rating.

OPTICS

Glass sealed-beam PAR36 lamp(s).


Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Catalog Number
Notes
Type

Unit Accessories

ELA Z

**Class I, Div. 2
Remote Fixture**



Specifications

Single

Length:	5-1/8" (mm)
Depth:	4-5/7" (116mm)
Height:	6-1/4" (mm)
Shipping Weight:	1-3/4lbs (0.77 kg)

Mounting Plate

Single-gang switch box

Width:	3-1/8"
Height:	5"

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

Lead times will vary depending on options selected. Consult with your sales representative.

Example: ELA Z N0806

ELA	Z		
Series	Fixture	Number of heads	Lamp type
ELA	Z Class 1, Div II remote head	(blank) Single T Twin	<u>PAR36 sealed-beam</u> N0606 6W/6V incandescent N0806 8W/6V incandescent N1212 12W/12V incandescent N1812 18W/12V incandescent N2512 25W/12V incandescent H0806 8W/6V halogen H1206 12W/6V halogen H0812 8W/12V halogen H1212 12W/12V halogen