Catalog Number	
Notes	
Type	

Contractor Select™

WMCL4/6

LED WALL CYLINDER LIGHT



Lithonia Lighting

FEATURES

- Switchable CCT (30K/40K/50K) offers warm, cool, and daylight in a single fixture
- Selectable Light Direction (Up/Down/Both)
- Integrated On/Off photocell
- UVOLT Driver (120-347)

Factory Settings	
Light Output	Up/Down
CCT	4000K
Photocell	On

Selectable Light Direction

Switchable CCT SWW2

Integrated Photocell

Catalog	Size	Wattage	Lumens @50K	LPW	Beam Spread	Color	CCT	Voltage	Photocell	Emergency Battery	Cicode	Lead Time
WMCL4 P1 SWW2 A45 UVOLT PE DDBXD M4	4"	19	2,479	130	45 Degree	Dark Bronze	30/40/50K	UVOLT	On/Off	No	2877PY	Stock
WMCL6 P1 SWW2 A45 UVOLT PE DDBXD M4	6"	31	4,728	153	45 Degree	Dark Bronze	30/40/50K	UVOLT	On/Off	No	2877R1	Stock
WMCL4 P1 SWW2 A75 UVOLT PE DDBXD M4	4"	19	2,433	128	75 Degree	Dark Bronze	30/40/50K	UVOLT	On/Off	No	2903FT	Stock
WMCL6 P1 SWW2 A75 UVOLT PE DDBXD M4	6"	31	4,520	146	75 Degree	Dark Bronze	30/40/50K	UVOLT	On/Off	No	2903FU	Stock

Specifications

INTENDED USE:
Provides years of maintenance-free illumination for outdoor use in residential & commercial applications. Ideal for applications such as lighting walkways and stairways for safety and security.

CONSTRUCTION:
Cast-aluminum housing with corrosion-resistant paint in dark bronze. Other colors available upon request

OPTICS:
80 CRI
Switchable CCTs 30K/40K/50K
Uplight and Downlight standard on unit and is field adjustable
Photocell is standard and can be turned on/off via switch
Glass lens protects the LED from moisture, dirt and other contaminants.

LUMEN MAINTENANCE:
The LED will deliver 70% of its initial lumens at 50,000 hour average LED life.

ELECTRICAL:
UVOLT driver operates on any line voltage from 120-347V
Operating temperature -40°C to 40°C.
4KV surge protection standard.
It is 0-10v dimmable.

INSTALLATION:
Surface mounts to universal junction box (provided by others).

LISTINGS:
UL Listed to U.S. and Canadian safety standards for wet locations.
Tested in accordance with IESNA LM-79 and LM-80 standards.
Fixture is IP66 rated for wet locations.

WARRANTY:
5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. The product images shown are for illustration purposes only and may not be an exact representation of the product.
Specifications subject to change without notice.

Dimensions

	4"	6"
Length (inches)	14.0	18.0
Diameter (inches)	4.0	6.0
Depth (inches)	6.1	8.1
Weight (lbs)	5.0	7.5

4"



6"



© 2025-2026 Acuity Brands Lighting, Inc. All rights reserved. Rev. 01/07/26