

DSXB

LED Bollard Luminaire

Designed to Perform. Built to Last.

The D-Series LED Bollard is designed to perform the way a bollard should – with zero uplift. An optical leap forward, this luminaire will meet the most stringent of lighting codes. The D-Series LED Bollard's rugged construction, durable finish and long-lasting LEDs will provide years of maintenance-free service.

Key Features:

- Energy savings up to 70% vs. comparable metal halide bollards; saves more than \$162 per luminaire, per year over 100W metal halide
- 20+ years expected service life (with lumen maintenance of L85/100,000 hours)
- Sturdy 8" aluminum shaft matches existing bollard dimensions with three-point mounting or a retrofit four-point solution
- Optional cold temperature (-20°C) emergency battery backup provides illumination along paths of egress during times of power loss

D-SERIES LED BOLLARD

DISTRIBUTION	SYMMETRIC	ASYMMETRIC
LUMENS (4000K)	3,009	2,335
INPUT WATTS	39W	31W

Learn more about our outdoor solutions at www.acuitybrands.com



Quick Facts:

- Replaces up to 100W MH bollards
- Input watts from 16 - 39W
- Asymmetric and Symmetric optical distributions
- Available in 3000K, 4000K & 5000K CCT and limited wavelength Amber LEDs'
- Designed with zinc-infused thermoset power coat finish providing superior resistance to corrosion and weathering

D-Series LED Bollard Luminaire

Ordering Information

EXAMPLE: DSXB LED 16C 700 40K SYM MVOLT DDBXD

DSXB LED														
Series	LEDs	Drive current		Color temperature		Distribution		Voltage	Control options		Options		Finish (required)	
DSXB LED	Asymmetric 12C 12 LEDs	350	350 mA	30K	3000K	ASY	Asymmetric	MVOLT	Shipped installed		Shipped installed		DWHXD	White
		450	450 mA	40K	4000K	SYM	Symmetric	120	PE	Photoelectric cell, button type	SF	Single fuse (120, 277, 347V)	DNAXD	Natural aluminum
		530	530 mA	50K	5000K		208	DMG	0-10V dimming driver (no controls)	DF	Double fuse (208, 240V)	DDBXD	Dark bronze	
	Symmetric 16C 16 LEDs	700	700 mA	AMBPC	Amber phosphor converted		240			ELCW	Emergency battery backup	H24	24" overall height	DDBTXD
						277	H30					30" overall height	DBLBXD	Textured black
						347	H36	36" overall height	DNATXD			Textured natural aluminum		

Wall Luminaire Accessories

Ordered and shipped separately.

MRAB U

Anchor bolts for DSXB

Please use the spec sheet at www.acuitybrands.com when ordering to ensure component compatibility for your desired configuration.



Visit www.lithonia.com for more information.