




Specifications

EPA:	0.96 ft ² 0.089 m ²
Length:	10" 254 mm
Width:	5-1/8" 130 mm
Height:	14-3/4" 375 mm
Height ² :	12-1/4" 318 mm
Weight:	24.1lbs

DIMENSIONS



YOKE FOOT PRINT

8100 RGBW

Yoke Mount; 36 LED

DMX Color Changing

HIGHLIGHTS

- Expected service life of over 100,000 hours
- Corrosion resistant, zinc-infused, durable TGIC thermoset powder coat finish
- Copper free aluminum housing
- IP67 rated
- 3G rated
- DMX Control/RDM

5
YEAR
warranty


IP67



LUMEN PACKAGES

	NSP	MFL	FL	WFL	HSP	HFL
Delivered Lumens	2859	2937	3212	2566	2983	2922
Watts	40	40	40	40	40	40
LPW	71	73	80	64	75	73

Note: Information based on all colors full on

ORDERING INFORMATION

EXAMPLE: 8100 36LED RGBW MVOLT NSP YM SMSA18 RDM BL

Model*	Lamp type*	LED Color*	Voltage*	Distribution*	Mounting*	Mounting Accessories
8100	36LED	RGBW 40K White (80CRI)	MVOLT (120-277 Volt)	NSP Narrow Spot MFL Medium Flood FL Flood WFL Wide Flood HSP Horizontal Spot HFL Horizontal Flood	YM Yoke Mount	EWM_ Ext. Wall Mt Available 18"- 48" in 6" increments PAR_/_/_ Pole Arm Round 4", 5", or 6" Pole 12", 18", or 24" length (i.e. PAR5/18) PAS_/_/_ Pole Arm Square 4", 5", or 6" Pole 12", 18", or 24" length (i.e. PAS4/24) PATR_/_/_ ¹ Pole Arm Twin Round 4", 5", or 6" Pole 12", 18", or 24" length (i.e. PATR6/12) PATS_/_/_ ¹ Pole Arm Twin Square 4", 5", or 6" Pole 12", 18", or 24" length (i.e. PATS6/12)
Mounting Accessories (Cont'd)		Accessories	Control	Finish*	Listing	
PMSA_	Pole Mt Splice Access	Internal ²	RDM ³ Remote device management	BL Black	STG Steel Gray	NT ^{4,5} Natatorium Construction
PMT	Pole Mount Tee	BD Barn Doors		BZ Bronze	TVG Terra Verde Green	
PSSA	Ped. Stanchion Splice Access	FGS Full Glare Shield		DDB Dark Bronze	WH White	
SMSA_	Stan. Mt Splice Access available 12"-48" in 6" increments	HGS Half Glare Shield		DNA Natural Aluminum	CF Custom	
SMT12/24'	Stanchion Mount Tee, ~ 12" height, 24" arm length	WRG Wire Rock Guard		GN Green	_Z ⁴ Zinc Undercoat (i.e. BLZ)	
SMT18/24'	Stanchion Mount Tee, ~ 18" height, 24" arm length			GR Gray	RALTB RAL Paint Finishes	
SMT24/24'	Stanchion Mount Tee, ~ 24" height, 24" arm length			SND Sand	Note: RALTB for pricing only, replace with applicable RAL call out when ready to order. See the RALBROCHURE for available options. It is recommended only use textures paint for Hydrel fixtures.	
ARJB	Architectural Junction Box					

*Required Catagories

Notes:

- Requires (2) two fixtures per mounting.
- Option is mutually exclusive.
- RDM = Field discoverable and field programmable DMX.
- Add Zinc undercoat for harsh environments.
- Natatorium rated Hydrel luminaires are built to withstand the elevated temperatures, high humidity and corrosive environments typically associated with natatoriums. Luminaires ordered with the "NT" nomenclature will have a zinc primer undercoat, zinc-infused super durable top coat, stainless steel hardware and IP67 ingress protection.

ELECTRICAL LOAD

			Current (A)			
Light Engines	Drive Current (mA)	System Watts	120	208	240	277
36LED	450mA	40	0.33	0.19	0.17	0.14

PERFORMANCE DATA

LUMEN OUTPUT

Lumen values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown, within the tolerances allowed by Lighting Facts. Actual performance may differ as a result of end-user environment and application. Contact factory for performance data on any configurations not shown here.
Photometric data for underwater lighting is based on the theoretical output of a dry fixture. The final output of a fixture placed in water is determined by the depth that the fixture is placed, the clarity and turbulence of the water and the color of the surrounding concrete and/or tile.

	Distribution	NEMA TYPE	Beam Angle (50%) H x V	Field Angle (10%) H x V	Watts	LPW	Delivered Lumens
All colors full on	NSP	1 X 1	6 X 7	17 X 17	40	71	2859
	MFL	3 x 3	21 X 21	37 X 37	40	73	2937
	FL	5 x 5	64 X 64	84 X 81	40	80	3212
	WFL	6 X 6	109 X 93	128 X 123	40	64	2566
	HSP	4 x 2	38 x 8	52 x 18	40	75	2983
	HFL	2 x 4	8 x 38	18 x 52	40	73	2922

TAKE CONTROL

Hydrel lighting solutions bring ease of use, innovation, and next-generation control features to commercial, underwater, and architectural outdoor applications. We offer a dedicated team of specification engineers to take you through lighting design, the specification process, to the installation of our fixtures. We simplify the complex and help you create the right layer of light for any outdoor lighting environment. Find the right architectural outdoor fixture, controls, and network connectivity with Hydrel Lighting Solutions.

RECOMMENDED CONTROLLERS

Easyl DMX touchscreen

<http://www.acuitybrands.com/products/detail/210270/Fresco/Easyl/Easyl-DMX512A-Show-Controller>



Easyl™ Solo: Is a standalone entry-level controller enabling show creation and playback directly at the LCD touchscreen.

Easyl™ Touch: features an astronomic time clock for automating shows and expands the controller's features by accepting inputs from remote button stations, and button station contact closure inputs.

Easyl™ Pro: is further enhanced by using Easyl Studio™ computer software to create multi-zone shows, and Easyl Pro features a 20 hour DMX512 capture from a theatrical console.

Fresco

<http://www.acuitybrands.com/products/detail/223381/Fresco/Fresco-Touchscreen-Lighting-Controllers>




FCS

- Create and edit 36 lighting scenes including intensity, color, and color temperature
- Integral astronomic timeclock with battery backup for system scheduling
- Direct DMX control for 1 universe (512 slots)
- Internal Bluetooth® radio for wireless App control

DMX WIRING - FLOOD


Up to 32 Fixtures Per DMX Line —
if there are more than 32 fixtures use a
splitter to create a new bus.



Notes:


1. DMX512 must be terminated by a 120 ohm resistor.
2. Signal cable by others, cable must be two-pair with a maximum capacitance of 12.8 pF/ft. and a impedance of 120 ohm.

DMX CONNECTION AND TERMINATION - WIRING DIAGRAM




MOUNTING OPTIONS


ARJB
ARCHITECTURAL JUNCTION BOX




PMSA
7" POLE MOUNT
WITH SPLICE ACCESS
EPA: 0.13




EWM
EXTENDED WALL MOUNT
18" - 36" LENGTHS




PAR/PAS & PATR/PATS (SINGLE & TWIN ARM)
POLE ARM ROUND/SQUARE
12" - 24" LENGTH AVAILABLE
EPA: 0.52 per 18" arm




PMT
POLE MOUNT TEE
EPA: 0.70




SMT
STANCHION MOUNT TEE
12", 18" or 24" HEIGHTS AVAILABLE




SMSA/PSSA
SMSA STANCHION AVAILABLE IN 12" - 48"
HEIGHTS (example: SMSA18, SMSA24)
PSSA Pedestal Stanchion - 7" HEIGHT




EXTERNAL ACCESSORIES




HGS - Half Glare Shield



FGS - Full Glare Shield



BD - Barn Doors



MRG - Wire Rock Guard

SPECIFICATIONS AND FEATURES

CONSTRUCTION: Die Cast Copper Free Aluminum (A360) Housing and Doors.

LED: RGBW (40K white 80CRI) LED array 40 input watts max.. Lumen maintenance of individual light sources has been independently tested using IESNA LM80 standards.

OPTICS: NEMA flood (2x2 through 6x6), horizontal flood (6x4), vertical flood (4x6).

LENS: Tempered borosilicate glass for maximum resistance to impact and thermal shock.

MOUNTING: Aluminum yoke & stainless steel locking hardware with infinite aiming adjustment capabilities and a wide array of mounting accessories. The 8100 series can withstand up to a 3G vibration load rating per ANSI/IEEE C136.31. Luminaires are provided with 10' of 16-3 ST-W cord for power supply and 10' of DMX data cable.

CONTROL: DMX512. Color control is achieved through standard DMX512 hardware, at a maximum of 44 frames per second. All channels have logarithmic power for finer color and intensity control. Compatible with the EasyL and Fresco controllers from Acuity. Controllers must be ordered separately.

ELECTRICAL: Integral ELDO RGBW power drive, MVOLT (120-277 volt) 50/60HZ LED PowerSupply, dims to zero. THD< 20%, class 2 driver with 100% to 0% dimming.

FINISH: Exterior parts are protected by a zinc-infused super durable TGIC thermoset powder coat finish that provides superior resistance to corrosion and weathering. A tightly controlled multi-stage process ensures a minimum 3 mils thickness for a finish that can withstand extreme climates without cracking or peeling.

LISTING: IP67, CSA, CSA_{US}

GOVERNMENT PROCUREMENT

BAA – Buy America(n) Act: Product qualifies as a domestic end product under the Buy American Act as implemented in the FAR and DFARS. Product also qualifies as manufactured in the United States under DOT Buy America regulations.

BABA – Build America Buy America: Product qualifies as produced in the United States under the definitions of the Build America, Buy America Act.

Please refer to www.acuitybrands.com/resources/buy-american for additional information.

WARRANTY: 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at:

www.acuitybrands.com/support/warranty/terms-and-conditions

Consult factory for details.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.