



HIGHLIGHTS


- 5-year limited warranty by Acuity Brands covering all components and construction
- 2', 4', 6' and 8' sections
- Up to 87 lm/W
- Two outputs available
- Seam eraser technology provides continuous illumination for long runs
- Flicker-free dimming to dark powered by eldoLED® driver
- Integrated nLight® module for system networking (optional)
- Modular light engine to allow for easy upgrades and replacement



eldoLED



DIMENSIONS




LUMEN PACKAGES Based on 80CRI 35K


Direct LED Output	500LMF	800LMF
Delivered Lumens Per Foot	630	863
Input Watts Per Foot	7.2	10.2
Lumens Per Watt	87	84

STANDARD DISTRIBUTION

100% Down



COMPANION LUMINAIRE(S)



CUSTOMIZATION

Ask us about the following possibilities: Higher lumen outputs, alternate section lengths, additional CCTs for LED boards, custom colors and other modifications.

SPECIFICATIONS

Housing

Extruded aluminum housing.

Luminaire Length

2', 4', 6' and 8' lengths.

Longer rows are comprised of starter, joiner and ender sections.

Source

Two LED lumen packages and three available color temperature options (3000K, 3500K and 4000K) in 80+ CRI and 90+ CRI options — all within 2.5 MacAdam ellipses.

Optics

Optical system consists of proprietary injection molded optic and high performance film.

Dimming Driver

eldoLED® driver (see page 3) provides “natural dimming” with smooth, continuous and flicker-free dimming to dark (0.1%). Syncing for controls: 2mA max. THD: < 20%. Insignificant inrush current at 120 and 277VAC. FCC Class A tested for EMI and RFI. When Control Input is specified driver will be set for linear dimming curve, if NLIGHT is specified driver will be set for logarithmic dimming curve.

For 0-10V and DALI details go to: PeerlessLighting.com/SOLOdrive

Controls and System Networking Options

For wired networking via Cat-5e, choose an integrated nLight® module (driver: ENNB).

One control module per 4' section or 40' maximum row.

Electrical

LED light engine — consisting of modular LED boards and eldoLED® dimming driver — is rated for 60,000 hours (L90) at 25° C ambient temperature. Specify 120V, 277V or 347V.

Environment

Ambient operating temperature between 0° C and 25° C. Suitable for dry and damp locations.

Validation

cCSAus listed. CSA tested to UL 1598 standards. LM-79 tested. Individual sections meet FCC Part 15 requirements.

Packaging

Recycled cardboard box and inserts. Biodegradable, protective luminaire bag. Recycled kraft paper tape.

Warranty

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

The product images shown are for illustration purposes only and may not be an exact representation of the product.

A+ Capable Luminaire

This item is an A+ capable luminaire, which has been designed and tested to provide consistent color appearance and out-of-the-box control compatibility with simple commissioning when used with Acuity Brands controls products. All configurations of this luminaire are calibrated and tested to meet the Acuity Brand's specification for chromatic consistency - including color rendering, color fidelity and color temperature tolerance around standard CIE chromaticity coordinates. To learn more about Acuity A+ standards, specifications, and testing.

To learn more about A+, visit www.acuitybrands.com/aplus.


*See ordering tree for details

MODEL NUMBER Example: OPRW G LOP 10FT 80CRI 35K 800LMF DARK ZT 120 SCT C041


Luminaire	Mounting Type	Linear Length Plan	Total Run Length	LED Color Rendering	LED Color Temperature	Direct LED Output
OPRW	G T-Grid ST Screw Slot Grid FL Flange (hard ceiling) GB Flangeless (hard ceiling)	LOP Linear optimized plan	__FT <i>Indicate luminaire row length in 2' increments. Ex: 10FT</i>	80CRI 80+ CRI 90CRI 90+ CRI	30K 3000K 35K 3500K 40K 4000K	500LMF 500 nominal direct lumens per foot 800LMF 800 nominal direct lumens per foot

Minimum Dimming Level	Control Input	Voltage	Wiring Option	Emergency Options	Color	Options
DARK Constant current, dimming to < 1% MIN1 Constant current, dimming to 1%	ZT ¹ 0-10V DALI ² DALI enabled NLIGHT ² nLight enabled 1. 0-10V will use linear curve 2. Will use logarithmic curve	120 120V 277 277V 347 ¹ 347V 1. J-box mount step down transformer (1) per section. Not available with NLIGHT or mounting types FL or GB.	SCT Single circuit	(Blank) None 1EC (1) Emergency circuit module 2EC (2) Emergency circuit module __EC __ Emergency circuit modules * Emergency type is installed in last 4' or 8' luminaire sections. * 4FT Individual fixture with EC Consult factory	C041 White white (low gloss) C099 ¹ Custom color RALTB ² RAL Paint Finishes 1. C099 for pricing only. Custom color chip and requested finish needs to be sent in to your Customer Care Rep and matched up with our paint department and customer approved before order is entered. Standard finish choice (s) Matte (C099M), Textured (C099T) or Semi Gloss (C099SG). 2. RALTB for pricing only. Replace with applicable RAL number and finish when ready to order. See the RAL BROCHURE for available color options. Standard finish choice (s) are Matte (RALxxxxM), Textured (RALxxxxT) or Semi Gloss (RALxxxxSG).	CSA ¹ Manufactured to Canadian Standards CP ^{2,3} Chicago Plenum GLR Fast blow GMF Slow blow HCF Healthcare facility cover 1. When chosen with EC entire section must be EC. EX: MSL8 section would need to be 2EC for entire section 2. Not available with nlight nor mounting types FL and GB. 3. Available with individual fixture only.


PHOTOMETRICS




G 500LMF 80CRI 35K
87 lm/W
2520 delivered lumens per
4' section
100% down



ST 500LMF 80CRI 35K
84 lm/W
2439 delivered lumens per
4' section
100% down



G 800LMF 80CRI 35K
84 lm/W
3449 delivered lumens per
4' section
100% down



ST 800LMF 80CRI 35K
82 lm/W
3339 delivered lumens per
4' section
100% down

COMPATIBLE nLIGHT COMPONENTS WITH INTEGRATED CONTROLS



nPODM DX WH



nPODM 2P DX WH



nPODM 4P DX WH

SensorSwitch.com/DataSheets/nPODM.pdf



nPODM 2L WH

SensorSwitch.com/DataSheets/nPODM-xL.pdf



nPOD GFX WH

SensorSwitch.com/DataSheets/nPOD-GFX.pdf

eldoLED COMPATIBILITY Additional control options with eldoLED 0-10V driver(s).

PeerlessLighting.com/eldoLED-compatibility